### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

Claim 1 (original). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for dividing the audio signal into at least two subband signals;

means for examining at least one sub-band signal with regard to a periodicity in the at least one sub-band signal by an autocorrelation function, to obtain rhythm raw-information for the sub-band signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the sub-band signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the sub-band signal, so that in the postprocessed rhythm raw-information an ambiguity in an integer plurality of a delay, to which an autocorrelation function peak is associated, is reduced, or a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

means for establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the sub-band signal and by using another sub-band signal of the at least two sub-band signals.

**3EST AVAILABLE COPY** 

Page 2 of 8

Claim 2 (currently amended). Apparatus according to claim 1, wherein the means for postprocessingcomprises postprocessing comprises:

means for calculating a version of the rhythm rawinformation of a sub-band signal spread by an integer factor; and

means for subtracting the version of the rhythm rawinformation of the sub-band signal spread by an integer factor larger than one, or a version of the rhythm rawinformation of the sub-band signal derived from this version, to obtain the postprocessed rhythm rawinformation for the sub-band signal.

Claim 3 (original). Apparatus according to claim 2, wherein means for subtracting is disposed to perform, prior to subtracting, a weighting of the spread version with a factor between zero and one, to generate the derived version.

Claim 4 (original). Apparatus according to claim 1, wherein means for postprocessing comprises:

means for calculating a version of the rhythm rawinformation compressed by an integer factor larger than one; and

means for adding the compressed version of the rhythm raw-information of the sub-band signal or a version derived therefrom to the rhythm raw-information of the sub-band signal, to obtain the postprocessed rhythm raw-information for the sub-band signal.

Claim 5 (original). Apparatus according to claim 4, wherein the means for adding is disposed to perform, prior to adding, a weighting of the compressed version of the

Page 3 of 8

rhythm raw-information by a factor between zero and one, such that a weighted compressed version of the rhythm raw-information is added to the rhythm raw-information of the sub-band signal to generate the derived version.

Claim 6 (original). Apparatus according to claim 1, further comprising:

means for evaluating a quality of the periodicity of the postprocessed rhythm raw-information, to obtain a significance measure for the sub-band signal,

wherein means for establishing is further disposed to establish the rhythm information of the audio signal by considering the significance measure of the sub-band signal.

Claim 7 (original). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

dividing the audio signal into at least two sub-band signals,

examining at least one sub-band signal with regard to a periodicity in the at least one sub-band signal by an autocorrelation function, to obtain rhythm raw-information for the sub-band signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the sub-band signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the sub-band signal, so that in the postprocessed rhythm raw-information an ambiguity in the integer plurality of a delay, to which an autocorrelation function peak is associated, is reduced, or a signal portion is added at an

Page 4 of 8

integer fraction of a delay, to which an autocorrelation function peak is associated; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the sub-band signal and by using a further sub-band signal of the at least two sub-band signals.

Claim 8 (currently amended). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal by adding a version of the rhythm raw information forged by an integer factor, so that in the postprocessed rhythm raw-information a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

means for establishing rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 9 (original). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-

Page 5 of 8

information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal, by subtracting a version of the rhythm raw-information weighted by a factor unequal one and spread by an integer factor larger than one; and

means for establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 10 (currently amended). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the audio signal by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal by adding a version of the rhythm raw information forged by an integer factor, so that in the postprocessed rhythm raw-information a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 11 (original). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal, by subtracting a version of the rhythm raw-information weighted with a factor unequal one and spread by an integer factor larger than one; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

# IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.